

#10-K-2216413

G28-003431
1434398

SPECIFICATIONS FOR 2009 ARCTIC CAT PROWLER 550 FLATBED,
OR EQUAL, UTILITY VEHICLE WITH WINCH

Utility Vehicle ^{MUST} should meet the following specifications: **(OR EXCEED)**

- Engine: 545cc, electronic fuel injection, 4-stroke, 4-valve, single-cylinder, liquid cooled
- Transmission: automatic
- Towing Capacity: rated at a minimum of 1500 lb. towing capacity
- Hauling Capacity: large rear flatbed with a 600 lb. hauling capacity
- Suspension: minimum of 10 inches of ground clearance
- Brakes: foot operated front and rear disk brakes
- Rims and Tires: Steel 14" wheels with 26x9R14 Goodyear MTR front tires and 26x11R14 Goodyear MTR rear tires **(OR EQUIVALENT)**
- Frame Protection: cover underneath running boards and entry areas
- Digital Gauges: digital display of critical operation indicators such as MPH, odometer, dual trip, clock, fuel level and gear position
- Cockpit: dual bucket seats with seat belts; center console with conveniently located dual 12V accessory outlets
- 4WD Controls: 2-wheel to 4-wheel drive should be electrically selectable with a 2wd/4wd/diff lock rocker switch for quick disengagement; reverse override button should be located on the console; rack and pinion steering
- 2-Inch Automotive Style Receiver Hitch: included
- Storage: a closeable glove box should be located in the console; additionally a molded tool kit box should be located in the passenger side seat
- Windshield: installation cost included in pricing
- Soft Top: installation cost included in pricing

Winch ^{MUST} should be Warn RT30 Winch, or equal, (front mounted to above specified vehicle) meeting the following specifications: **(MINIMUM)**

- Motor: 12V DC (.9 hp) with a rated line pull of 3000 lb.
- Controls: remote control, 10 ft lead and handlebar mounted mini rocker
- Gear Train: 3-stage planetary
- Gear Ratio: 154:1
- Clutch: sliding pin and ring gear
- Brake: roller disk
- Drum Diameter Length: 2.0" – 2.9"
- Rope: galvanized steel wire 3/16" x 50'
- Fairlead: roller
- Recommended Battery: 12 Amp/hr minimum
- Duty Cycle: intermittent
- Battery Leads: 6 gauge
- Finish: steel grey powder coat
- Warranty: lifetime